



Benefit:

- Digital Precision Control
- Quick Change Tool and Die rack
- Energy Saving and Safety Operation
- TUV CE Approved

SAMWAY P32D

| | | | |
|----------------------|-----------------|---------------------|--------------|
| Main Specification | SAMWAY P32D | Control by Pressure | Optional |
| Max Hydraulic Hose | 2" 4SP | Noise Level dBA | 65 |
| Crimping Range mm | 4-87 | Protection Class | IP56 |
| Die Type | P32 | L*W*H mm | 680*600*1400 |
| Master Die Length mm | 80 | Weight KG | 300 |
| Max Opening mm | +32 | | |
| Motor KW | 4 | | |
| Crimping Force KN | 2200 | | |
| Crimpings Per Hour | 1200 | | |
| Control | Digital Control | | |
| Foot pedal | Included | | |
| Die Rack | Included | | |
| Quick Change Tool | Included | | |
| Backstop Device | Optional | | |

Order No.

| | |
|--------------------------------------|-----------|
| 220V, 400V, 415V, 440V, 480V 3 phase | :00001310 |
| 110V 60hz single phase | :00001311 |
| 220V 50/60hz single phase | :00001312 |

Standard Die Sets Included:

| | | | | | | | | | | | | | |
|---------|----|----|----|----|----|----|----|----|----|----|----|----|----|
| Die No. | 10 | 13 | 16 | 19 | 22 | 26 | 30 | 39 | 45 | 52 | 57 | 64 | 69 |
| Length | 55 | 55 | 55 | 55 | 55 | 55 | 75 | 75 | 90 | 90 | 90 | 90 | 90 |