



Benefit:

- Precision Digital Control
- Quick Change Tool and Die rack
- Designed for Mass Production
- Energy Saving and Safety Operation
- CE Approved

SAMWAY FP120D

| | | | |
|----------------------|---------------------------|---------------------|---------------|
| Main Specification | SAMWAY FP120D | Mirror | Included |
| Max Hydraulic Hose | 2" 6SP | Control by Pressure | Optional |
| Crimping Range mm | 4-87 | Noise Level dBA | 65 |
| Die Type | P32 | Protection Class | IP56 |
| Master Die Length mm | 100 | L*W*H mm | 860*1000*1600 |
| Max Opening mm | +65 | Weight KG | 1220 |
| Motor KW | 5.5 by SIEMENS | | |
| Crimping Force KN | 2800 | | |
| Crimpings Per Hour | 2400 | | |
| Control | Precision Digital Control | | |
| Foot pedal | Included | | |
| Die Rack | Included | | |
| Quick Change Tool | Included | | |
| Backstop Device | Included | | |

| Order No. | |
|--------------------------------------|-----------|
| 220V, 400V, 415V, 440V, 480V 3 phase | :00001710 |
| 220V 50/60hz single phase | :00001712 |

Standard Die Sets Included:

| | | | | | | | | | | | | | | | |
|---------|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|-----|
| Die No. | 10 | 13 | 16 | 19 | 22 | 26 | 30 | 39 | 45 | 52 | 57 | 64 | 69 | 74 | 78 |
| Length | 55 | 55 | 55 | 55 | 55 | 55 | 75 | 75 | 90 | 90 | 90 | 90 | 90 | 100 | 100 |